beetronics
Professional Display Solutions

Beetronics
2 Lakeside Drive, Park Royal
London, NW10 7FQ
United Kingdom

Phone: 020 3608 7495
Fax: 020 3695 1651
E-mail: info@beetronics.co.uk
Web: www.beetronics.co.uk



22 inch monitor metal

Item number: 22HD7M

This 22 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 22 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 22HD7M can be connected via HDMI, VGA, BNC or RCA connections.

- 1920 x 1080 resolution (Full HD)
- Input: HDMI, VGA, BNC and RCA
- Desktop, flush and wall mountable
- 511 x 309 x 39 mm







© 2021 Beetronics

beetronics
Professional Display Solutions

Beetronics
2 Lakeside Drive, Park Royal
London, NW10 7FQ
United Kingdom

Phone: 020 3608 7495
Fax: 020 3695 1651
E-mail: info@beetronics.co.uk
Web: www.beetronics.co.uk

GENERAL	
Manufacturer	Beetronics
Item number	22HD7M
Previous model	22HDM
Product name	22 inch monitor metal
Warranty	2 years

PANEL	
Type	Matte, LED-IPS
Screen diagonal	21,5 inches (546 mm)
Aspect ratio	16:9 (4:3 adjustable)
Native resolution	1920 x 1080
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	100 PPI
Viewing angle	178° horizontal, 178° vertical
Colour encoding system	PAL/NTSC/SECAM
Brightness	300 cd/m2
Contrast	3000:1

© 2021 Beetronics

beetronics
Professional Display Solutions

Beetronics
2 Lakeside Drive, Park Royal
London, NW10 7FQ
United Kingdom

Phone: 020 3608 7495
Fax: 020 3695 1651
E-mail: info@beetronics.co.uk
Web: www.beetronics.co.uk

CONNECTIVITY	
HDMI	✓ 1x
VGA	✓ 1x
BNC (CVBS)	✓ 1x
RCA video	✓ 1x
AUX input	✓ 1x
AUX output	✓ 1x
USB	✓ 1x (MP4, AVI, MKV, MOV, MPG, MP3, WMA, JPG, JPEG, PNG)

SIZE & WEIGHT	
Colour	Black
Weight	5290 gram (5960 gram with stand)
Width	511 mm
Height	309 mm (+0 to 30 mm with stand)
Thickness	39 mm
Display dimensions	479 x 270 mm

FEATURES AND FUNCTIONS	
Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically

© 2021 Beetronics

beetronics
Professional Display Solutions

Beetronics
2 Lakeside Drive, Park Royal
London, NW10 7FQ
United Kingdom

Phone: 020 3608 7495
Fax: 020 3695 1651
E-mail: info@beetronics.co.uk
Web: www.beetronics.co.uk

POWER	
Input voltage	DC 9-33V
Power supply	Input: 110-240V ~ 50/60Hz - Output: 12V-2A
Consumption	<15 Watt (0.5 Watt standby)

ENVIRONMENTAL	
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 90% non-condensing

MOUNTING	
Wall mount	✓ VESA (100 mm)
Flush mount	✓ Mounting strips included
Stand	✓ Adjustable and detachable


CERTIFICATIONS & STANDARDS	
Certifications	CE, FCC, RoHS, REACH

PACKAGE CONTENT	
Includes	Monitor, Stand, Remote control, Mounting strips, Mains adaptor, Manual

© 2021 Beetronics

Beetronics
2 Lakeside Drive, Park Royal
London, NW10 7FQ
United Kingdom

Phone: 020 3608 7495
Fax: 020 3695 1651
E-mail: info@beetronics.co.uk
Web: www.beetronics.co.uk



© 2021 Beetronics